

DS AIR RELAY SWITCHES

HOW TO ORDER DS SERIES AIR RELAY SWITCHES

Group 1	Group 2	Group 3	Group 4	Group 5	Group 6	Group 7	Group 8
Non standard allocation	Model	Air Inlet/Outlet Ports	Switch Type	Range Code (values in bar)	Valve Type	Pressure Port Material / Size	Diaphragm
<input type="checkbox"/> Reserved for non-standard options not covered in catalogue. Will be given by manufacturer, only after agreement of supply details with customer.	DS = Dual Air Relay switch	A = PU tube dia. 4mm OD	PF2 = air relay switch, fixed differential with scale in bar PF3 = air relay switch, fixed differential with scale in psi PA2 = air relay switch, adjustable differential with scale in bar PA3 = air relay switch, adjustable differential with scale in psi	H01 = (0.1 - 1.0) H02 = (0.1 - 1.5) H03 = (0.2 - 2.6) H04 = (0.2 - 3.6) H07 = (0.5 - 7.0) H10 = (0.5 - 10.0) H15 = (1.0 - 15.0) H30 = (5.0 - 25.0)	P1 = NC valve P2 = NO valve P3 = SPDT valve	S1 = SS316 / 1/4" BSP(F) S2 = SS316 / 1/4" NPT(F)	*0 = Neoprene *1 = Teflon 2 = SS 316L

eg. A dual air relay switch with fixed differential having 0.1 bar to 1 bar pressure range, with NC valve, SS316 pressure housing with 1/4" BSP port size & neoprene diaphragm shall be specified by

Group 1	Group 2	Group 3	Group 4	Group 5	Group 6	Group 7	Group 8
<input type="checkbox"/>	DS	A	PF2	H01	P1	S1	0

Please specify full model number to avoid ambiguity.