

OEM HIGH RANGE PRESSURE SWITCHES

EZ__A / EX__A

General information:

EZ /EX series pressure switches are housed in pressed steel powder coated enclosure and are recommended for panel mounting or indoor service. The repeat accuracy is better than $\pm 1.5\%$ FSR. A 3/8" BSP cable entry is provided for cables and a terminal strip suitable for wired ends is provided inside the enclosure. Pressure port is 1/4" NPTF standard.

Features:

- Compact
- SS316 & Teflon as standard wetted parts
- Electrical rating : 5A, 250 VAC; 0.2A, 250VDC (res.)
- Pressure port: 1/4" NPTF

Range Selection Table

Model Code	† Range psi	*Approximate Maximum Differential psi	* Adjustable Differential psi	Maximum Working Pressure psi
EZ4A	3.0 - 50.0	3.0	-	200.0
EZ7A	7.0 - 100.0	6.0	-	200.0
EZ15A	15.0 - 200.0	6.0	-	350.0
EZ30A	70.0 - 350.0	6.0	-	500.0
EX7A	7.0 - 100.0	-	10.0 - 90.0	200.0
EX15A	15.0 - 200.0	-	20.0 - 150.0	350.0
EX30A	70.0 - 350.0	-	40.0 - 150.0	500.0

*Minimum differential increases with setpoint (Graphs available on request)

† rising pressure for EZ series; falling pressure for EX series

HOW TO ORDER EZ__A/EX__A OEM HIGH RANGE PRESSURE SWITCHES

Please specify model code as per range selection table above.