

MZ HIGH PROOF HIGH RANGE PRESSURE SWITCHES

RANGE SELECTION TABLE

Range Code	Range bar (psi)	Differential* bar (psi)	Maximum Working Pressure bar (psi)
		Approximate Maximum for "A8" microswitch	
PP5	0.1 - 0.5 (1.45 - 7.25)	0.20 (2.90)	70 (1015.26)
P01	0.1 - 1.0 (1.45 - 14.50)	0.20 (2.90)	70 (1015.26)
P02	0.1 - 1.5 (1.45 - 21.76)	0.40 (5.80)	70 (1015.26)
P03	0.2 - 2.6 (2.90 - 37.71)	0.40 (5.80)	70 (1015.26)
P04	0.2 - 3.6 (2.90 - 52.21)	0.50 (7.25)	70 (1015.26)
P07	0.5 - 7.0 (7.25 - 101.53)	1.00 (14.50)	70 (1015.26)
P10	0.5 - 10.0 (7.25 - 145.04)	1.00 (14.50)	70 (1015.26)
P15	1.0 - 15.0 (14.50 - 217.56)	1.5 (21.76)	70 (1015.26)
P30	5.0 - 25.0 (72.52 - 362.6)	1.5 (21.76)	70 (1015.26)

*Minimum differential increases with setpoint (Graphs available on request), results for neoprene diaphragm.